



i-SENSYS
FAX-L390

Make your business more productive with laser faxing and printing. The Super G3 modem, large fax memory and paper capacity plus Automatic Document Feeder make it ideal for heavy duty use - with Departmental ID Management to control costs and ensure security.

- Super G3 plain paper laser fax - 3 seconds per page transmission*
- 510-page* fax memory
- 18 ppm laser printer: 600 dpi print quality
- 500-sheet paper capacity for heavy-duty use with 50-page Automatic Document Feeder
- Departmental ID Management: control your costs and ensure security by restricting fax use to authorised personnel
- Speed dialling: 31 one touch/169 coded dial keys
- Ultra High Quality imaging with 256 grey scales for faxing photos and diagrams with maximum detail
- All-in-One cartridge
- Compact and robust design

* Based on ITU-T Standard Chart No.1



i-SENSYS
FAX-L380S

The i-SENSYS FAX-L380S provides high speed, high quality laser faxing and printing - complete with a range of features for ease and efficiency. Control costs and enhance security by restricting fax use to authorised staff, with the Departmental ID Management function.

- Plain Paper laser fax with Super G3 modem - 3 seconds per page transmission*
- 510-page* fax memory
- 18 ppm laser printer: 600 dpi print quality
- Departmental ID Management: control your costs and enhance security by restricting fax use to authorised personnel
- 250-sheet paper capacity, 50-page Automatic Document Feeder
- Speed dialling: 31 one touch/100 coded dial keys
- Ultra High Quality imaging with 256 grey scales for faxing photos and diagrams with maximum detail
- All-in-One cartridge
- Compact and robust design

* Based on ITU-T Standard Chart No.1



Laser Fax Specifications Chart



	i-SENSYS FAX-L3000IP	i-SENSYS FAX-L3000	i-SENSYS FAX-L390
FAX UNIT TYPE			
Compatibility	Group 3	Group 3	Group 3
Applicable Line	PSTN	PSTN	PSTN
FAX SCANNING FEATURES			
Automatic Document Feeder	A4 & A3 Duplex ADF 50 sheets A4, 20 sheets A3 (80 g/m ²)	50 sheets (80 g/m ² paper) Max. A4	50 sheets
Effective Scanning Width	297mm	210mm	208mm
Scanning Speed	45ipm	37ipm	Approx. 2 sec./page, Approx. 25 pages per minute
Fax Resolution	Standard, Fine, Photo, Super fine, Ultra fine	Standard, Fine, Photo, Super fine, Ultra fine	Standard, Fine, Super fine, Ultra fine
Image Processing System	UHQ (Ultra High Quality)	UHQ (Ultra High Quality)	UHQ (Ultra High Quality)
Halftone	256 shades of grey	256 shades of grey	256 shades of grey
FAX PRINTING FEATURES			
Printing Method	Mono Laser Beam Printing	Mono Laser Beam Printing	Mono Laser Beam Printing
Print Speed	22 pages per minute	22 pages per minute	18 pages per minute
Print Resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
Paper Capacity	500 sheets paper cassette, Optional cassette (500 sheets) Multipurpose tray: 100 sheets (auto sheet feeder)	500 sheets paper cassette, Optional cassette (500 sheets) Multipurpose tray: 100 sheets (auto sheet feeder)	500 sheets Auto Sheet Feeder, Manual Feed: 1 sheet
Print Cartridge	Cartridge 714 All-in-One cartridge	Cartridge 714 All-in-One cartridge	Cartridge T All-in-One cartridge
Yield	Approx. 4,500 pages based on 5% coverage	Approx. 4,500 pages based on 5% coverage	Approx. 3,500 pages based on ISO/IEC19752 (Approx. 5,250 pages with Toner Save on)
Toner/Ink Saver Mode	YES	YES	YES
Auto Image Reduction On Reception	YES (100 to 50%, 70%)	YES (100 to 50%, 70%)	YES (100 to 75%)
TRANSMISSION/RECEPTION FEATURES			
Transmission Speed	3 seconds per page with 33.6 Kbps modem (based on ITU-T Standard Chart No. 1)	3 seconds per page with 33.6 Kbps modem (based on ITU-T Standard Chart No. 1)	3 seconds per page with 33.6 Kbps modem (based on ITU-T Standard Chart No. 1)
Compression Method	MH, MR, MMR, JBIG	MH, MR, MMR, JBIG	MH, MR, MMR, JBIG
Memory Transmission/Reception	YES	YES	YES
Quick Memory Transmission	YES	YES	YES
Fax Memory	1,500 pages (based on ITU-T Standard Chart No.1)	512 pages (based on ITU-T Standard Chart No.1) Max. 1,500 pages with optional UFRIL-TP/KIT-X1	Memory Transmission: 510 pages (based on ITU-T Standard Chart No. 1), Memory Reception: 510 pages (based on ITU-T Standard Chart No. 1)
Memory Backup	YES (Approx. 3 hours)	YES (Approx. 3 hours)	YES (1 hour)
Optional Memory	NO	NO	NO
SECURITY AND MANAGEMENT FEATURES			
Dual Access	YES	YES	YES
Error Correction Mode (ECM)	YES	YES	YES
TELEPHONE FEATURES			
Delayed Transmission	YES	YES	YES (Max. 142 locations)
Sequential Broadcast	YES (201 locations, Max. 501 locations with Optional SEND kit)	YES (201 locations)	YES (Max. 142 locations)
Polling	Transmission: NO Reception: NO	NO NO	YES (Memory)
Dept. ID Management	YES	YES	YES
System Administrator ID	YES	YES	YES
Reports	1-Touch list, coded dial list, group dial list, user's data list, dept. info list, activity report, TX/RX report, forwarding conditions	1-Touch list, coded dial list, group dial list, user's data list, dept. info list, activity report, TX/RX report, forwarding conditions list	Activity Report, Transmission Report, Reception Report, Multi Transaction Report, Memory Clear Report, Doc.Memory/Speed Dial/Group Dial List
One-touch Dials	80 locations	80 locations	31 locations
Coded Dials	200 dials, Max. 500 dials with optional SEND kit	200 dials	169 locations
Redial	YES (Automatic and Manual)	YES (Automatic and Manual)	YES (Automatic and Manual)
Built-in Answering Machine	NO	NO	NO
Fax/Tel. Auto Switch	YES	YES	YES
Answering Machine Hook-up	YES	YES	YES
Remote Reception	YES	YES	YES
Telephone Handset	Option	Option	Option
Other Features	NO	NO	Password user restriction
COPY FEATURE			
Copy Speed (Mono)	22 pages per minute	22 pages per minute	18 pages per minute
Multiple Copy	Up to 99 copies	Up to 99 copies	Up to 99 copies
Reduction/Enlargement	50%, 70%/141%, 145%	50%, 70%/141%, 145%	YES (Preset ratios 50% - 200%)
PC RELATED FEATURES			
PC Interface	USB 2.0 Hi-Speed	USB 2.0 Hi-Speed (printing and PC faxing require optional KIT)	USB
Printer Function (Printer Language)	PCL 5e, PCL 6 & UFRIL-IT	Optional (UFRIL-IT)	YES (CARPS)
Supported OS	Windows 98/ME/2000/XP/Server 2003/Vista/ Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (English driver only and online distribution only. No scanning)	Windows 98/ME/2000/XP/Server 2003/Vista/ Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (English driver only and online distribution only. No scanning)	Windows 98/ME/2000/XP/Vista
Print Speed	22 pages per minute	22 pages per minute	18 pages per minute
Print Resolution	1,200 x 600 dpi (enhanced)	1,200 x 600 dpi (enhanced)	600 x 600 dpi (1,200 x 600 dpi enhanced)
NETWORK FEATURES			
Network Connectivity	Built-in network interface card	With optional UFRIL-TP/KIT-X1	With optional Axis 1650 Print server
Functionality	Printing & PC Faxing, Optional SEND functionality	Printing & PC Faxing with optional UFRIL-TP/KIT-X1	Network printing
Type	Ethernet (10BaseT/100BaseT)	Ethernet (10BaseT/100BaseT)	NO
Network protocols	TCP/IP	TCP/IP	NO
GENERAL FEATURES			
Dimensions Without Trays (W x D x H)	520 x 492 x 451mm	520 x 492 x 451mm	441 x 466 x 392mm
Weight	Approx. 24kg	Approx. 24kg	Approx. 12.1kg
Power Consumption	Max.: Approx.1,010W, Standby: Approx.17W, Sleep: Approx. 3W (3.5W with optional SEND kit)	Max.: Approx.1,010W, Standby: Approx.17W, Sleep: Approx. 3W	Max.: Approx. 800W, Standby: Approx. 10W