Large Format Print Solutions ideal for CAD & GIS

iPF750 / iPF755

you can

The imagePROGRAF iPF750 and iPF755 are 36"/A0 printers, delivering class leading productivity, exceptional quality, accuracy and an advanced set of features to ensure an excellent return on investment.





Key Features

- Manage costs and track ROI Full accounting and eMaintenance software included.
- Space saving Unique compact design to fit anywhere.
- User Friendly Simple roll paper loading system and control the printer from the front.
- Maximise productivity -"Hot Swap" ink tanks, changeable during production
- Minimise printer downtime with media mismatch detection (iPF755).
- High capacity basket with stacking functionality to prevent damage to prints.
- Highly accurate with 0.02mm minimum line width and +/-0.1% line accuracy.
- Integrate with your office applications with Microsoft Office Plug-in.
- HP-GL/2 and HP-RTL Compatible: -
 - Capable of handling large vector files
 - HP-GL/2 pallet and pen settings
 - HP-GL/2 and HP-RTL nesting (iPF755).
 - HP-GL/2 auto-rotation.





Specifications: iPF750 / iPF755

Ink Type Maximum Print Resolution Printing Speed (A0 Roll, Full Colour Image) Plain Paper

Coated Paper

Dimensions, Weight (Net) $W \times D \times H (mm), (kg)$

> Dimensions, Weight (Packaged) W x D x H (mm), (kg)

Power Supply Input power Power consumption Standby power consumption (At the low power mode) 100 V - 120 V 220 V - 240V Power off (standby)

> Operational Environment Acoustic Noise Acoustic power Minimal Line Width Line Accuracy

Operation Panel Display Large Language on operation panel Displayable Language on LCD

> Printer Language Interface USB Type Mode Connector type Ethernet Standard

> > Protocol

Operating Systems Supported

Macintosh Memory Standard Memory HDD Print head Model Туре Head configuration Nozzle pitch Nozzle per chip Droplet size Head replacement

Dye and pigment reactive ink: BK, MBK x 2, C, M, Y 2,400 x 1,200 dpi

0.48 (Draft mode) 1.14 (Standard Mode) 1.14 (Draft Mode)

3.51 (High Quality Mode)

iPF750: Main unit with a basket open and a printer stand 1,304(W) x 870(D) x 1,062(H)mm ; Weight: approx. 62.9kg iPF755: Main unit with a basket open and a printer stand 1,304(W) x 870(D) x 1,062(H)mm; Weight: approx. 63.1kg

iPF750: Main unit 1.434(W) x 830(D) x 770(H)mm: Weight: approx. 75.1kg iPF755: Main unit 1,434(W) x 830(D) x 770(H)mm;

Weight: approx. 75.3kg

iPF750: Stand and Basket 1.380(W) x 760(D) x 240(H)mm: Weight: approx. 16.8kg iPF755: Stand and Basket 1,380(W) x 760(D) x 240(H)mm;

Weight: approx. 16.8kg

AC 100 - 240 V (50/60 Hz) 140W or less

5W or less 6W or less

1W or less (In compliance with Executive Order of the President of the United States of America)

Temperature: 15 - 30°C, Humidity: 10 - 80% (Condensation free)

Operation: 50 dB (A) or less, Standby: 35 dB (A) or less Operation: 6.6 Bels or less 0.02mm (Theoretical value)

+0.1 % or less (User adjustments necessary, Printing environment media must match that used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper,

CAD translucent matte film only.) LCD: 160 x 128 dots, Key x 13, LED x 5

US-English, Japanese US-English, French, German, Italian, Spanish, Chinese (simplified), Korean, Japanese (Kanji), Russian GARO, HP-GL/2, HP RTL

Built-in Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer Series B (4 pins)

Built-in

IEEE 802.3 10base-T

IEEE 802.3u 100base-TX / Auto-Negotiation IEEE 802.3ab 100base-T / Auto-Negotiation IEEE 802.3 x Full Duplex IPX/SPX (Netware 4.2(J), 5.1(J), 6.0(J))

SNMP (Canon-MIB), HTTP, TCP/IP, AppleTalk

2000 (32)/XP (32 & 64)/Server 2003 (32 & 64)/Server 2008 (32 & 64)/Vista (32 & 64) OS X (32 & 64)

256Mb 80Gb (iPF755)

Bubble-jet on demand 6 colours integrated type (6 chips per print head x 1 print head) 1.200dpi MBK: 5,120 nozzles, Other Colours: 2,560 nozzles each

4 pl per colour User replacement

Ink tank	
Model	

PEI-102 (130ml): MBK/BK/C/Y, PEI-104 (130ml): M

Media handling

Roll paper Cut sheet Media type Roll paper One roll, top-loading, front output

Top-feeding, front output (Manual feed using media locking lever)

Standard Paper 90gsm Matt Coated Paper 90gsm

Glossy Photo Quality Paper 190gsm / 240gsm / 300gsm Satin Photo Quality Paper 190gsm / 240gsm / 300gsm

Pearl Photo Paper 260gsm Matt Coated Paper 120gsm / 140gsm / 180gsm Opaque White Paper 120gsm High Resolution Self-adhesive Graphic Paper 140gsm

High Resolution Barrier Paper 180gsm

Glossy Proofing Paper 195gsm Semi-Glossy Proofing Paper 195gsm / 255gsm

Media Size Roll paper (width)

Cut sheet

ISO: A3, A2, A2+, A1, A0, JIS: B4, B2, B1, ARCH: 24", 30", 36" Others: 10", 14", 16", 17", Banner (300mm) ISO: A4, A3, A3+, A2, A2+, A1, A0, B4, B3, B2, B1 DIN: C4, C3, C2, C1, C0

JIS: B4, B3, B2, B1, B0 ANSI: 8.5 x 11", 8.5 x 14", 11 x 17", 13 x 19", 17 x 22", 22 x 34", 28 x 40", 34 x 44" ARCH: 9 x 12", 12 x 18", 18 x 24", 24 x 36", 26 x 38", 27 x 39", 30 x 42", 36 x 48"

Photo: 20 x 24", 18 x 22", 14 x 17", 12 x 16", 10 x 12", 10 x 15" 16 x 20" (US Photo size), Poster: 20 x 30", 30 x 40", 300 x 900mm,

Media Thickness Roll paper & Cut sheet: 0.07 - 0.8mm

Maximum Outside Diameter of Roll Paper Media Core Size Media Width

Internal diameter of roll core: 2" / 3" Roll paper: 254 (10") - 914.4 (36")mm Cut sheet: 203.2 (8") - 917 (DIN C0)mm

Minimum regular format size (Vertical)

Roll paper: 203.2mm (8") Cut Sheet: 279.4mm (11"): Letter size (long side)

Maximum Printable Paper Length

Margins (Top, Bottom, Sides) Recommended area

Roll paper: Top: 20mm, Bottom: 5mm, Side: 5mm

Cut sheet: Top: 20mm, Bottom: 23mm, Side: 5mm Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm Roll paper (borderless print): Top: 0mm, Bottom: 0mm, Side: 0mm Cut sheet: Top: 3mm, Bottom: 23mm, Side: 3mm

Roll paper: 18m (Varies according to the OS and application) Cut sheet: 1.6m (Varies according to the OS and application)

Media width for borderless printing

Printable area

10"(254mm), B4(257mm), A3(297mm), Banner(300mm), 14"(356mm), A2(420mm), A2+/17"(432mm), B2(515mm) A1(594mm), 24"(610mm), B1 (728mm), A0(841mm), 36" (914mm)

Option Roll Holder Set (for both 2 and 3" core roll media)

RH2-33

Ink Tank Print Head Maintenance Cartridge PFI-102 (130ml): MBK/BK/C/Y, PFI-104 (130ml): M

MC-10

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final are subject to change without notice.™ and ⊚: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.









Canon Europa N.V. www.canon-europe.com

English-UK Edition 00000 © Canon Europa NV 2009

