# HIGH-PERFORMANCE EIO HARD DISK

Equipped with versatile time saving features and robust functionality, the HP High-Performance EIO Hard Disk lets you securely control when and how documents are printed on your EIO equipped HP peripherals.

## Enhanced productivity

Save time and resources by preventing costly errors. When printing multiple copies, use the Proof-and-Hold option to review the first printed copy before printing the rest of the job.

Reduce time-consuming trips between the computer and printer. With the Quick Copy feature, print up to 999 additional copies of the last print job directly from the product's control panel.

Store frequently printed documents on the hard disk. The Stored Jobs feature enables on-demand printing from the product's control panel without any computer involvement.

## Powerful performance

Enjoy fast throughput speeds. The high-speed Ultra 100 Parallel ATA hard disk helps keep your peripheral running at peak performance.

Get quick, convenient access to commonly printed information. The hard disk effortlessly stores forms, logos, and fonts.

Depend on HP reliability. Backed by telephone support and a one-year return-to-HP warranty, the HP High-Performance Hard Disk delivers the quality and reliability you expect from HP.

HP printing and imaging systems help you create powerful, professional communications easily. Printers, supplies, accessories, and services are designed together to work together and are invented to meet your business needs.

# HP HIGH-PERFORMANCE EIO HARD DISK

## Technical specifications

| | |
|---|---|
| **Part number** | J6073G |
| **Interface** | EIO |
| **What's in the box** | HP High-Performance Parallel ATA EIO Hard Disk, installation guide |
| **Supported peripherals** | HP Color LaserJet 3000, 3800, 4650, 4700, 5550, 9500, 4730 MFP, 9500 MFP; HP LaserJet 4250, 4350, 5200, 9050, 4100 MFP, 4345 MFP, 9040 MFP, 9050 MFP, 9055 MFP, 9065 MFP |
| **Environmental ranges** | |
|    Operating temperature | 5 to 50° C (41 to 122° F) |
|    Storage temperature | 0 to 55° C (32 to 131° F) |
|    Operating relative humidity | 8 to 90% |
|    Storage relative humidity | 8 to 90% |
| **Certifications** | |
|    Electromagnetic compatibility | USA (FCC Title 47, Part 15 Class B), Europe (see DOC), Taiwan (CNS 13438), Australia (AS3548), New Zealand (NZS3548), Korea (EMI law No. 1996-98) |
|    Safety | Complies with EN 60950 |
| **Dimensions (width x depth x height)** | 8.6 x 15.0 x 3.6 cm (3.4 x 5.9 x 1.4 in) |
| **Weight** | 0.15 kg (0.4 lb) |
| **Warranty** | One-year limited hardware warranty, return to HP |

To learn more, visit www.hp.com